

DuPont™ Cyrel® Microflex 1320

State-of-the-Art Mounting Equipment




DuPont™ Cyrel® Microflex 1320

DuPont Advanced Printing brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates ([analogue and digital](#)), [Cyrel® platemaking equipment](#), [Cyrel® round sleeves](#), Cyrel® plate mounting systems and the revolutionary [Cyrel® FAST thermal system](#).

DuPont™ Cyrel® Systems: Higher quality at high speed.

The Cyrel® Microflex 1320 is designed with customer needs in mind and is easy to install, support, maintain and operate. It is robust, extremely cost effective and reliable.

DuPont™ Cyrel® Microflex 1320



Floor Plan

Benefits

- Maximum plate width 1,320 mm
- Repeat length 280 – 1,016 mm
- Extremely precise mounting with outstanding repeatability
- Robust and easy to maintain
- Simple to operate
- Optimum productivity

Product Features

DuPont™ Cyrel® Microflex 1320 can mount photopolymer plates up to a nominal maximum size of 1,320 mm (52 inch) in width and maximum repeat length of 1,016 mm (40 inch).

The Cyrel® Microflex 1320 is highly productive and extremely precise, for mounting of plates onto cylinders or sleeves with a high repeatability. Two digital, motor controlled cameras indicate plate positions with each having an enlargement factor of 40X. No PC expertise is required to operate the unit, and it is safe and easy to use. Fast Mount Button and software controlled tail stock for semi-automatic sleeve change are included in the standard machine.

Available Options

- Rubber roller to support plate mounting
- Air coupling for "sleeve-on-sleeve" workflow
- Adaption to W+H Easy Reg workflow
- Fixed shaft (Cantilever) design
- Secomea module for remote access
- Extended repeat up to 1250 mm

IMPORTANT!

At the time of the order placement, it is essential to obtain the cylinder drawings of the cylinders to be used with the system!

DuPont™ Cyrel® Microflex 1320

State-of-the-Art Mounting Equipment

Technical Data		
General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® Microflex 1320	
SAP Article Number	MH51366	
Packing	Crated	
Max. nominal plate width	1,320 mm – 52 inch	
Repeat length	280 mm – 1,016 mm / 11 inch – 40 inch	
Electrical (field configurable)	400 V, 50/60 Hz	3Ph / N / PE connection wires 5 x 2.5 mm ²
Power (nominal)	1.2 kW	
Current (nominal load)	5.2 Amp	
Grounding	< 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
Exhaust	NA	
Environmental Data	Temperature range 15°C to 30°C (59°F to 86°F)	Relative humidity From 40% to 60% non-condensing
Compressed Air Supply	7 bar minimum	101.5 psi
Air consumption for the machine	12 L per min – 0.423 scfm	
Air consumption for the sleeve change	300 L per min – 10.59 scfm	
Dimensions: D W H Weight	Uncrated: 2,930 mm (115.4") 910 mm (35.9") 1,690 mm (66.6") 2,200 kg – 4,850 lbs	Crated: 3,600 mm (141.7") 1,600 mm (63.0") 2,370 mm (93.3") 2,600 kg – 5,732 lbs
Colour	DuPont Grey, side plates in DuPont Red	

www.cyrel.eu

For more information on DuPont™ Cyrel® or other DuPont Advanced Printing products, please contact your local representative.

DuPont de Nemours (Deutschland) GmbH

Tel: +49 (0) 6102 18 1592

DuPont (U.K.) Limited

Tel: +44 (0) 1438 734000